

		200 L			300L			400L			500L		
		DX0	DX1	DX2	DX0	DX1	DX2	DX0	DX1	DX2	DX0	DX1	DX2
Width	A	560	560	600	600	600	600	650	650	650	700	700	700
Height	B	1325	1325	1325	1560	1560	1560	1810	1810	1810	1828	1828	1828
Hot Outlet, PTR, Top Sensor	C	1105	1105	1105	1340	1340	1340	1565	1565	1565	1585	1585	1585
Top Coil	D			950			1240			1370			1390
Anode	E	940	906	1005	1040	1040	1140	1170	1190	1270	1190	1210	1290
Mid Sensor	F	780	795	825	920	920	880	1000	1000	1010	1080	1020	1030
Top Coil	G			700			690			820			840
Bottom Coil or Solar Return	H	830	745	600	880	880	590	910	910	686	930	930	705
Secondary Return	I	700	665	475	800	800	465	830	830	496	850	850	515
Bottom Sensor	J	400	410	400	400	400	400	430	430	430	450	450	450
Bottom Coil or Solar Flow	K	300	340	350	340	340	340	370	370	370	390	390	390
Element Port	L	300	300	310	300	300	300	330	330	330	350	350	350
Cold Inlet and Secondary Flow	M	230	230	230	220	220	220	250	250	250	275	270	270
Drain	N	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5

